

ePilot Pilot Scale Solutions

Optimizing bioprocessing outcomes with innovative engineering and precise regulation for pilot plants.



STR ePilot BR

Microbial / Cellular · 10 L up to 50 L

High-performance automatic bioreactor with cellular and microbial configurations, an excellent choice for pilot scale development and production.



STR Single Use ePilot STR SU

Dual Purpose \cdot 30 L and 50 L

A scalable dual-purpose bioreactor featuring precise temperature control, efficient agitation and wide instrumentation, designed for 30 and 50 L single use bags.



TFF ePilot TFF

Hollow Fiber / Cassette · Up to 6.5 m² of surface area

Automatic pilot Tangential Flow Filtration system with high efficiency and versatility for bioprocessing, featuring options for concentration, diafiltration, and membrane surface adjustments.




Adaptable and interconnected

Build a pilot plant that grows with your needs. ePilot and ePlus equipment work hand-in-hand to offer scalability, efficiency, and flexibility. Transition from simple processes to advanced setups without compromising process control or quality.



A tangential flow filtration system for pilot-scale operations, perfect for concentration and diafiltration processes. Designed for ease of use and high-performance membrane filtration.





Clean-in-place system ensuring hygiene, compliance, and minimal downtime.



Mixer for precise, uniform blending of media and buffers in bioprocesses.





ePilot bioreactor single use ePilot tangential flow filtration

Multi use

Vessels

Single use

Vessels

Cassette: 0.5-2.5 Hollow Fiber: 0.1-6.5

Filter area (m²)

1200x2020x910

Size in mm

600x1687x595

Size in mm

1546x1412x524

Size in mm

 $10\cdot 20\cdot 30\cdot 50$

Volumes (L)

30 . 50

Volumes (L)

50 - 200

Volumes (L)

Stainless steel

Housing Material

Stainless steel

Housing Material

Versatile Holder Accommodating

Range of filter options

eSCADA Advanced

Software

eSCADA Advanced

Software

1x Variable Speed 1x Fixed Speed

Peristaltic Pump

4x Variable Speed

Peristaltic Pumps

4x Integrated Variable Pumps
3x External Variable Pumps

Peristaltic Pumps

230VAC | 50Hz | 9A

Power Supply

Servomotor 400-750

Motor (W)

TECNIC eBAG 3D STR

Compatibility

20 LPM

Recirculation Pump

Global reach, local support

Our global distributor network is ready to provide specialized products and support in your region. Please contact your local distributor to work with TECNIC.

sales@tecnic.eu







